

AD-753 499

MEASURING HEAD

Yu. Z. Tenenbaum, et al

Foreign Technology Division
Wright-Patterson Air Force Base, Ohio

22 November 1972

DISTRIBUTED BY:

NTIS

National Technical Information Service
U. S. DEPARTMENT OF COMMERCE
5285 Port Royal Road, Springfield Va. 22151

AD753499

FTD-HT-23-1324-72



FOREIGN TECHNOLOGY DIVISION



MEASURING HEAD

by

Yu. Z. Tenenbaum and V. S. Demidov



Reproduced by
**NATIONAL TECHNICAL
INFORMATION SERVICE**
U S Department of Commerce
Springfield VA 22151

Approved for public release;
Distribution unlimited.

UNCLASSIFIED
Security Classification

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Foreign Technology Division Air Force Systems Command U. S. Air Force		2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
3. REPORT TITLE MEASURING HEAD		2b. GROUP	
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Translation			
5. AUTHOR(S) (First name, middle initial, last name) Tenenbaum, Yu.Z.; Demidov, V.S.			
6. REPORT DATE 8 September 1969		7a. TOTAL NO. OF PAGES 26	7b. NO. OF REFS
8a. CONTRACT OR GRANT NO.		8b. ORIGINATOR'S REPORT NUMBER(S) FTD-HT-23-1324-72	
b. PROJECT NO. 7343		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
c.			
d.			
10. DISTRIBUTION STATEMENT Approved for public release; distribution unlimited.			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY Foreign Technology Division Wright-Patterson AFB, Ohio	
13. ABSTRACT The measuring head containing a housing (in which there are series connected mechanisms - one a sine mechanism and the other a link mechanism with a drive lever - and two gears), an indicator, a scale, and a pan selection unit is distinguished by the fact that the lever of the link mechanism is made adjustable in length to increase accuracy.			

DD FORM 1473
1 NOV 68

UNCLASSIFIED
Security Classification

Security Classification

Measurement Gear

ii

UNCLASSIFIED

Security Classification

FTD-HT- 23-1324-72

EDITED TRANSLATION

FTD-HT-23-1324-72

MEASURING HEAD

By: Yu. Z. Tenenbaum and V. S. Demidov

English pages: 2

Source: USSR Patent No. 288210 (Appl. No.
1362515/25-28, September 8, 1969),
1971, pp. 1-2.

Requester: ASD

Translated by: SSgt René E. Courville

Approved for public release;
distribution unlimited.

THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DIVISION.

PREPARED BY:

TRANSLATION DIVISION
FOREIGN TECHNOLOGY DIVISION
WP-AFB, OHIO.

FTD-HT-23-1324-72

Date 22 Nov 19 72

MEASURING HEAD

Yu. Z. Tenenbaum and V. S. Demidov

The invention pertains to the area of measuring technique for linear measurements of dimensions.

An existing measuring head contains a housing (in which there are series connected mechanisms - one a sine mechanism and the other a link mechanism with a drive lever - and two gears), an indicator, a scale, and a gap selection unit.

The proposed head is distinguished by the fact that the lever of the link mechanism is made adjustable in length. This increases accuracy.

The drawing depicts a functional diagram of the proposed head.

It contains housing 1, sine mechanism 2, link mechanism 3 with drive lever 4 and two gears 5 and 6, indicator 7, scale 8, and gap selection unit 9. The lever of the link gear is made adjustable in length.

The gears are set up so that the ratio of the lever length to the center-to-center distance of the hinges equals three. In this case the nonlinearity error on the scale is not observed on account of its small value. A definite type of error is added because of the turning of gear wheel 10. On the basis of the amplitude of error caused by error in the gear wheel, the length of the lever is adjusted, in this case restoring the required gear ratio.

Object of the Invention

The measuring head containing a housing (in which there are series connected mechanisms - one a sine mechanism and the other a link mechanism with a drive lever - and two gears), an indicator, a scale, and a gap selection unit is distinguished by the fact that the lever of the link mechanism is made adjustable in length to increase accuracy.

